

## TECHNICAL DATA SHEET



## Double A 80 - FSC<sup>®</sup> certified

### PRODUCT SPECIFICATIONS

Properties	Method	Values
Basis weight (g/m <sup>2</sup> )	ISO 536	80
Caliper (μm)	ISO 534	107 ± 2
Whiteness CIE	ISO 11475	165 ± 2
Brightness D65 (%)	ISO 2470	111 ± 1
Opacity (%)	ISO 2471	95 ± 1
Moisture (%)	ISO 287	4.5
Bendtsen Roughness (ml/min)	ISO 8791-2	70 ± 10
Kodak Stiffness MD (mN.m)		0.45
Kodak Stiffness CD (mN.m)	ISO 5629	0.16
Bending resistance MD (mN)		150
Bending resistance CD (mN)	ISO 2493	55

These values are indicative only  
Valid from January 2019

### CERTIFICATIONS

Alizay mill is certified according to ISO 9001, ISO 14001 and ISO 50001.  
**Double A** is a permanent paper which fulfills requirements of ISO 9706.  
**Double A** fulfills requirements of NF EN 12281 for both high and low volume machines.

**Double A** is a paper certified « FSC<sup>®</sup> Mix » with credits method.  
The Double A Alizay mill FSC CoC has number FCBA-CoC-000414.

